





共 通 规 格	
精度等级	JIS N8 级 (JIS B 1702-1 : 1998) *
齿 形	全齿高齿
压 力 角	20°
材 料	快削黄铜 (C3604)
热 处 理	—
齿面硬度	(80HV 以上)


* 模数 0.8 以下的产品精度是与表记精度相当的产品。



S3T



S1



S1T

产品型号	模数	齿数	形状	孔径	轮毂径	分度圆直径	齿顶圆直径	齿宽	轮毂长	全长		
				A _{H7}	B	C	D	E	F	G		
BSS0.5-15A	m0.5	15	S3T	3	8.5	7.5	8.5	3	11	14		
BSS0.5-16A		16			9	8	9					
BSS0.5-20		20	S1	4	8.5	10	11		7 11	10 14		
BSS0.5-20A			S3T	3	11							
BSS0.5-22A		22	S1T	3	9	11	12		7	10		
BSS0.5-24B				24	4	10	12				13	
BSS0.5-25		25	S1	4	11	12.5	13.5					
BSS0.5-30		30	S1	4	13	15	16					
BSS0.5-30A			S1T	3	12							
BSS0.5-30B			S1T	4	12							
BSS0.5-30C			S1T	5	12							
BSS0.5-38A		38	S1T	4	16	19	20					
BSS0.5-40		40	S1	4	17	20	21					
BSS0.5-50A		50	S1T	4	22	25	26					
BSS0.8-20	m0.8	20	S1	5	13.5	16	17.6	4			8	12
BSS0.8-24B		24			16	19.2	20.8					
BSS0.8-25		25			17	20	21.6					
BSS0.8-30		30	S1	5	20	24	25.6					
BSS0.8-30A			S1T	4								
BSS0.8-40		40	S1	5	20	32	33.6					
BSS1-16B	m1	16	S1T	5	12	16	18	6	8	14		
BSS1-18B		18		6	15	18	20					
BSS1-20C		20		6	16	20	22					
BSS1-30B		30	S1T	6	25	30	32					
BSS1-40A		40	S1T	6	28	40	42					

螺孔		容许转矩 (N · m)	容许转矩 (kgf · m)	侧隙 (mm)	质量 (kg)	产品型号
尺寸	J	弯曲强度	弯曲强度			
M3	2.5	0.058	0.0059	0~0.10	0.0054	BSS0.5-15A
—	—	0.065	0.0066		0.0062	BSS0.5-16A
—	—	0.091	0.0093		0.0043	BSS0.5-20
M3	2.5	0.10	0.011		0.0098	BSS0.5-20A
M3	3.5	0.12	0.012		0.0054	BSS0.5-22A
—	—	0.12	0.013		0.0063	BSS0.5-24B
—	—	0.16	0.016		0.0077	BSS0.5-25
—	—	0.16	0.016		0.011	BSS0.5-30
M3	3.5	0.22	0.022	0~0.10	0.010	BSS0.5-30A
M3	3.5	0.23	0.024		0.0099	BSS0.5-30B
M4	3.5	0.31	0.031		0.0092	BSS0.5-30C
M3	3.5	0.31	0.032		0.018	BSS0.5-38A
—	—	0.40	0.041		0.020	BSS0.5-40
—	—	0.43	0.043		0.033	BSS0.5-50A
M3	4	0.55	0.056		0.014	BSS0.8-20
—	—	0.79	0.081		0.021	BSS0.8-24B
M4	4	0.52	0.053		0.024	BSS0.8-25
M4	4	0.62	0.063	0.08~0.18	0.034	BSS0.8-30
M4	4	0.73	0.074		0.035	BSS0.8-30A
M4	4	1.28	0.13		0.046	BSS0.8-40
M4	4	1.86	0.19		0.015	BSS1-16B
—	—	0.026	0.026	0.08~0.18	0.021	BSS1-18B
—	—	0.065	0.065		0.026	BSS1-20C
—	—	0.10	0.10		0.065	BSS1-30B
—	—	0.10	0.10	—	0.10	BSS1-40A